



CERTIFIED WEIGHT REPORT

Part Number: 70021
Lot Number: 021417
Description: Aroclor 1260

Solvent(s): Methanol
Lot# DN615

Expiration Date: 021427
Recommended Storage: Ambient (20 °C)
Nominal Concentration (µg/mL): 1000
NIST Test ID#: 822-275872-11

Weight(s) shown below were combined and diluted to (mL): 200.0 0.058 Balance Uncertainty
0.058 Flask Uncertainty

		021417
Formulated By:	Lawrence Barry	DATE
		021417
Reviewed By:	Pedro L. Rentas	DATE

Compound	RM#	Lot Number	Nominal Conc (µg/mL)	Purity (%)	Uncertainty Purity	Target Weight (g)	Actual Weight (g)	Actual Conc(µg/mL)	Expanded Uncertainty (+/-) (µg/mL)	MSDS Information (Solvent Safety Info. On Attached pg.)		
										CAS#	OSHA PEL (TWA)	LD50
1. Aroclor 1260	21	020491JC	1000	100	0.2	0.19999	0.20006	1000.3	4.1	11096-82-5	0.5mg/m3	ori-rat 1315mg/kg

Run 22, "P70021 L021417 [1000µg/mL in methanol]"

Run Length: 35.00 min, 21000 points at 10 points/second.
Created: Fri, Feb 17, 2017 at 9:16:11 PM.
Sampled: Sequence "021617-GC3M1", Method "GC3-M1".
Analyzed using Method "GC3-M1".

- The certified value is the concentration calculated from gravimetric and volumetric measurements unless otherwise stated.
- Standards are prepared gravimetrically using balances that are calibrated with weights traceable to NIST (see above).
- Standards are certified (+/-) 0.5% of the stated value, unless otherwise stated.
- All Standards, after opening ampule, should be stored with caps tight and under appropriate laboratory conditions.
- Uncertainty Reference: Taylor, B.N. and Kuyat, C.E., "Guidelines for Evaluating and Expressing the Uncertainty of NIST Measurement Result," NIST Technical Note 1297, U.S. Government Printing Office, Washington, DC, (1994).

Comments

GC3-M1 Analysis by Melissa Stonier
Column ID SPB-608 30 meter X 0.53mm X5µm film thickness
Flow rates: Helium (carrier) = 5mL/min, Helium (make-up) = 25mL/min
Hydrogen (make-up) = 30mL/min, Air (make-up) = 350mL/min
Oven Profile: Temp 1 = 150°C (Time 1 = 4 min), Temp 2 = 290°C (Time 2 = 13.5 min)
Rate = 8°C/min, Total run time = 35 min
Injector temp. = 200°C, FID Temp. = 300°C. FID Signal = Edaq Channel 1
Standard injection = 1.5µL, Range=3

